

# Breakout Box BOB MS 6



- ▶ Optimised packaging facilitates a low-profile design with compact, lightweight housing
- ▶ Robust 4 mm standard jacks for measuring leads
- ▶ Signal integrity of high-speed data links ensured by product-specific version
- ▶ Standard configurations and fully customized versions available
- ▶ No more lost jumpers due to patented 90° rotatable connectors

We developed this BOB version for use with Engine Control Units MS 6 and a second version for use with Engine Control Units MS 6 EVO. They differ in their internal structure and cannot be interchanged.

## Technical Specifications

### Mechanical Data

Size	355 x 270 x 50 mm
Weight	4,100 g
4 mm standard jacks for measuring leads	176
Ethernet connectors	4
Ethernet wire	2 x inclusive

USB connectors	2
USB jumper	inclusive

### Connectors and Wires

Wire length L	2 x 60 cm
---------------	-----------

### Legal Restrictions

Due to embargo restrictions, sale of this product in Russia, Belarus, Iran, Syria, Libya, Afghanistan, and North Korea is prohibited.

### Ordering Information

**Breakout Box BOB MS 6**  
Order number **F02U.V02.294-01**

#### Represented by:

**Europe:**  
Bosch Engineering GmbH  
Motorsport  
Robert-Bosch-Allee 1  
74232 Abstatt  
Germany  
motorsport@bosch.com  
www.bosch-motorsport.de

**North America:**  
Bosch Engineering North America  
Motorsport  
38000 Hills Tech Drive  
Farmington Hills, MI 48331-3417  
United States of America  
motorsport@bosch.com  
www.bosch-motorsport.com

**Asia-Pacific:**  
Bosch Engineering Japan K.K.  
Motorsports Department  
1-9-32 Nakagawachuo, Tsuzuki-ku  
Yokohama-shi  
Kanagawa, 224-8601  
Japan  
motorsport@jp.bosch.com  
www.bosch-motorsport.jp

**Australia, New Zealand and South Africa:**  
Robert Bosch Pty. Ltd  
Motorsport  
1555 Centre Road  
Clayton, Victoria, 3168  
Australia  
motor.sport@au.bosch.com  
www.bosch-motorsport.com.au