

Wire Potentiometer WP 120

The WP 120 is a wire potentiometer which is designed to measure position, direction or rate of motion of moving mechanical components.

This sensor converts mechanical movement into electrical signal using a stainless steel cable wound on a threaded drum that is coupled to a precision rotary sensor. Hence the electrical output is proportional to the distance travelled.

The advantage of this WP is its compact style which allows for flexible and easy installation. Due to its small size, precise measurement is possible even in difficult applications.



Application	
Application	0 ... 120 mm
Temperature range	-15 ... 60 °C
Max. cable tension	2.2 N

Electrical Data	
Power supply	5 V
Power supply max.	25 V
Nominal resistance	1 kΩ
Resistance tolerance	0.15 %
Non-linearity	1 %

Mechanical Data	
Weight w/o cable	85 g
Possible mechanical range	120 mm
Mounting	2 x Ø 4 & Ø 4.8
Life expectancy	1 x 10 ⁶ cycles
Dimensions	45.7 x 44.5 x 59.7 mm

Connectors and Cables

Connector	ASL 6-06-05PA-HE
Connector loom	ASL 0-06-05SA-HE
Pin 1	Us
Pin 2	Gnd
Pin 3	Sig
Pin 4	-
Pin 5	-
Sleeve	DR-25
Cable size	AWG 24
Cable length L	15 ... 50 cm

Various motorsports and automotive connectors on request.

Please specify the requested cable length with your order.

Application Hint

The WP 120 can be connected directly to most electronic control units and data logging systems.

The angle of the displacement cable should be in the range of $\pm 5 \dots 10^\circ$ from normal direction to avoid damaging the housing.

Do not allow the cable to snap back (freely retract). This will cause damage and void the warranty. Tension must be maintained on the cable at all times.

Please find further application hints in the offer drawing (<http://www.bosch-motorsport.com>).

Part Number

WP 120 **F 01T A21 250**

